



BIN AERATORS - VB OLI



> SCAN QR CODE
FOR MAINTENANCE
& INSTALLATION
DOCUMENTS

- The fluidizers allow the preventive fluidification of bulk powder.
- They are suitable for dry, fine-grained products such as cement, lime, pigments, flour, etc.
- Fluidization is used as a preventive or active measure.



We reserve the right to change specifications and dimensions without notice.

APPARENCE				AIR CONSUMPTION								TEMPERATURE			
Model	Fig.	Membrane Colour	Stem Matter	0.8 bar (11.6 psi)		2 bar (29 psi)		4 bar (58 psi)		6 bar (87 psi)		°C		°F	
				l/min	Cfm	l/min	Cfm	l/min	Cfm	l/min	Cfm	Min.	Max.	Min.	Max.
VBS	A	White	Aluminium	600	20	800	28	950	33	1150	40	-40	170	-40	338
VBSI	A	White	Stainless steel	600	20	800	28	950	33	1150	40	-40	170	-40	338
VBSIHT	A	Red	Stainless steel	600	20	800	28	950	33	1150	40	-40	235	-40	455
VBSIMD	A	Blue	Stainless steel	600	20	800	28	950	33	1150	40	-40	170	-40	338
VBE	B	White	Nylon	-	-	100	3.53	150	5.29	250	8.82	-40	80	-40	176
VBSME	C	White	Nylon	130	4.6	150	5.3	-	-	-	-	-40	80	-40	176
VBSM	D	White	Aluminium	130	3.5	150	5	-	-	-	-	-40	170	-40	338
VBSMI	D	White	Stainless steel	130	3.5	150	5	-	-	-	-	-40	170	-40	338
VBSMIHT	D	Red	Stainless steel	130	3.5	150	5	-	-	-	-	-40	235	-40	455
VBSMIMD	D	Blue	Stainless steel	130	3.5	150	5	-	-	-	-	-40	170	-40	338

