



PNEUMATIC LINEAR VIBRATORS FP FINDEVA



> SCAN QR CODE FOR MAINTENANCE & INSTALLATION DOCUMENTS

- Unidirectional vibration offers an efficient and reliable solution for the conveying and dosing of materials.
- Number of vibrations per minute permanently adjustable by setting operating pressure



We reserve the right to change specifications and dimensions without notice.

PNEUMATIC SPECIFICATIONS					DIMENSIONS (mm)							
Model	Frequency 6 Bar	Linear Force		Conso. Air	Fig.	A	B	C	D	E	F	Weight
	Vib. /min	KG	N	l/min								
FP-12-S	9300	9,3	92	25	1	71	34	M8	G 1/8"	G 1/8"	-	0,15
FP-12-M	6700	7,5	74	19	1	81	34	M8	G 1/8"	G 1/8"	-	0,17
FP-12-L	5400	8	81	20	1	94	34	M8	G 1/8"	G 1/8"	-	0,21
FP-18-S	7700	19	187	57	1	81	42	M10	G 1/8"	G 1/8"	-	0,30
FP-18-M	5900	20	188	52	1	94	42	M10	G 1/8"	G 1/8"	-	0,35
FP-25-S	4600	21	206	46	1	109	42	M10	G 1/8"	G 1/8"	-	0,42
FP-25-M	5500	43	416	93	1	98	50	M12	G 1/8"	G 1/4"	-	0,55
FP-25-L	4200	52	504	87	1	116	50	M12	G 1/8"	G 1/4"	-	0,67
FP-35-S	3700	61	594	93	1	136	50	M12	G 1/8"	G 1/4"	-	0,82
FP-35-M	5800	106	1038	162	1	98	65	M12	G 1/4"	G 1/4"	-	0,92
FP-35-L	4600	110	1080	141	1	116	65	M12	G 1/4"	G 1/4"	-	1,13
FP-12-S	3600	108	1066	135	1	136	65	M12	G 1/4"	G 1/4"	-	1,38
FP-50-M	2800	118	1660	190	2	154	90	M16	G 1/4"	G 1/4"	∅ 84	3,30
FP-60-M	2700	221	2170	270	2	154	110	M16	G 1/4"	G 3/8"	∅ 94	4,25
FP-95-M	2800	627	6150	450	3	157	150	-	G 3/8"	G 3/8"	∅ 140	9,46

