



PNEUMATIC TURBINE VIBRATORS GT FINDEVA



> SCAN QR CODE FOR MAINTENANCE & INSTALLATION DOCUMENTS

- High efficiency with minimal air consumption.
- The bearing mounting allows the vibrators to be used without lubricated air.
- Wide range to suit your needs.



We reserve the right to change specifications and dimensions without notice.

PNEUMATIC SPECIFICATIONS					DIMENSIONS (mm)								
Model	Frequency 6 Bar	Centrifugal Force		Air Consum.	A	B	C	D	E	F	G	H	Weight
	Vib. /min	KG	N	l/min	-	-	-	-	-	-	-	-	KG
GT 4	15 000	20	200	83	40	28	70	56	10	6	1/8"	1/8"	0,167
GT 6	12 500	21	210	83	40	28	70	56	10	6	1/8"	1/8"	0,161
GT 8	46 000	296	2910	112	50	33	86	68	12	7	1/8"	1/8"	0,255
GT 10	37 500	244	2400	112	50	33	86	68	12	7	1/8"	1/8"	0,258
GT 10 S	25 000	198	1950	112	50	33	86	68	12	7	1/8"	1/8"	0,27
GT 13	33 000	380	3730	290	65	42	113	90	16	9	1/8"	1/8"	0,555
GT 16	24 000	322	3160	290	65	42	113	90	16	9	1/4"	1/4"	0,566
GT 16 S	17 000	275	2700	290	65	42	113	90	16	9	1/8"	1/8"	0,603
GT 20	23 000	563	5520	455	80	56	128	104	16	9	1/4"	1/4"	1,076
GT 25	17 000	517	5070	455	80	56	128	104	16	9	1/4"	1/4"	1,112
GT 25 S	13 000	500	4900	455	80	56	128	104	16	9	1/4"	1/4"	1,193
GT 30	16 000	769	7540	745	100	73	160	130	20	11	3/8"	3/8"	2,2
GT 36	13 000	733	7190	745	100	73	160	130	20	11	3/8"	3/8"	2,3
GT 36 S	8300	765	7500	745	100	73	160	130	20	11	3/8"	3/8"	2,525
GT 40	9500	999	9800	970	120	83	194	152	24	17	3/8"	3/8"	3,696
GT 48	9700	1070	10500	970	120	83	194	152	24	17	3/8"	3/8"	3,858
GT 48 S	6300	1223	12000	970	120	83	194	152	24	17	3/8"	3/8"	4,274

