



PNEUMATIC TURBINE VIBRATORS PVT VIBRAMOTORS



ATEX



DEVELOPPED IN FRANCE

> SCAN QR CODE
FOR MAINTENANCE
& INSTALLATION
DOCUMENTS

- Turbine vibrators offering the best compatibility with third-party equipment.
- Turbine special profile with high quality grooved bearings and high temperature resistant anodized housing.
- High quality bearings greased for life dispensing with any maintenance and lubrication



We reserve the right to change specifications and dimensions without notice.

PNEUMATIC SPECIFICATIONS					DIMENSIONS (mm)							
Model	Frequency 6 Bar	Centrifugal Force		Air Consum.	A	B	C	D	E	F	G	Weight
	Vib. /min	KG	N	l/min	-	-	-	-	-	-	-	KG
PVT 8	45 120	131	1285	120	50	86	34	68	12	1/8	7	0,3
PVT 10	33 900	148	1454	120	50	86	34	68	12	1/8	7	0,3
PVT 12	30 600	127	1254	120	50	86	34	68	12	1/8	7	0,3
PVT 13	28 425	191	1849	295	65	113	42	90	16	1/4	9	0,6
PVT 16	21 300	222	2183	295	65	113	42	90	16	1/4	9	0,6
PVT 19	19 846	203	1999	295	65	113	42	90	16	1/4	9	0,7
PVT 20	22 560	348	3415	450	80	128	56	104	16	1/4	9	1,2
PVT 25	16 860	409	4016	450	80	128	56	104	16	1/4	9	1,2
PVT 29	16 200	400	3927	450	80	128	56	104	16	1/4	9	1,2
PVT 30	17 162	716	7030	780	100	160	75	130	20	3/8	13	2,3
PVT 36	12 860	861	8445	780	100	160	75	130	20	3/8	13	2,3
PVT 40	11 982	793	7776	780	100	160	75	130	20	3/8	13	2,3

