



ELECTRIC VIBRATORS MV 750 VIBRAMOTORS



- Industrial vibrators offering the best compatibility with third-party equipment.
- Adjustment of the weight simple and fast thanks to our system exclusive percentage indicator dial.
(See Instruction)
- Range available in three-phase power supply. From 101 Kg and up to 7 T of centrifugal force.
- Quality performance and craftsmanship for the most competitive price on the market.



*Contact us to obtain the values in 60 Hz / or in 230 Volts triple-phase. **Working Moment = 2x static moment.

	MECHANICAL SPECIFICATIONS					ELECTRICAL SPECIFICATIONS				
	RPM	Model	Centrifugal Force		Static Moment**	Weight	Nominal Voltage	Maximal Current	Capacitor	Maximal Power
	50 Hz *	Cf /Poles	KG	N	kgmm	KG	V	A	Delta/Wye	kW
T H R E E P H A S E	750	MV 150/0.75	101	1000	167	21	230/400	1.14	Δ / Y	0.23
		MV 250/0.75	203	2000	284.2	29	230/400	0.9	Δ / Y	0.35
		MV 400/0.75	183	1800	420	34	230/400	0.9	Δ / Y	0.35
		MV 650/0.75	458	4500	685	63	230/400	1.2	Δ / Y	0.5
		MV 900/0.75	611	6000	938.5	70	230/400	1.23	Δ / Y	0.65
		MV 1300/0.75	917	9000	1498	90	230/400	2.2	Δ / Y	1.2
		MV 2100/0.75	1529	15000	2337	150	230/400	2.81	Δ / Y	1.5
		MV 3100/0.75	2141	21000	3401	201	230/400	4.5	Δ / Y	2
		MV 3800/0.75	2549	25000	4192	219	230/400	6	Δ / Y	2.5
		MV 4200/0.75	3059	30000	4648	268	230/400	7.15	Δ / Y	2.9
		MV 5300/0.75	3569	35000	5826	289	230/400	8	Δ / Y	4
MV 6500/0.75	4588	45000	7179	308	230/400	8.78	Δ / Y	5		
MV 10000/0.75	7138	70000	11002	422	230/400	13.5	Δ / Y	6,81		

The technical information, diagrams and images present in this document are the exclusive property of Vibraxion Sarl. Any reproduction is non-contractual.



ELECTRIC VIBRATORS MV 750 VIBRAMOTORS

We reserve the right to change specifications and dimensions without notice.

DIMENSIONS (mm)														
Model	A	B	ΦG	C	D	E	F	H	I	L	M	N	Cable	Fig
MV150/0.75	105	140	13	330	170	196	20	92	174	166	78	160	M20×1.5	C
MV250/0.75	120	170	17	386	208	210	22	96	185	192	97	170	M20×1.5	C
MV400/0.75	120	170	17	450	208	210	22	96	185	192	129	170	M20×1.5	C
MV650/0.75	140	190	17	442	230	260	26	124	240	218	112	222	M25×1.5	C
MV900/0.75	140	190	17	486	230	260	26	124	240	218	134	222	M25×1.5	C
MV1300/0.75	155	225	22	558	275	290	30	140	256	250	154	236	M25×1.5	C
MV2100/0.75	155	255	23.5	687	304	314	30	147	285	277	205	265	M32×1.5	C
MV3100/0.75	180	280	26	678	332	354	32	170	330	312	183	311	M32×1.5	C
MV3800/0.75	180	280	26	728	332	354	32	170	330	312	208	311	M32×1.5	C
MV4200/0.75	200	320	28	704	385	402	40	203	394	360	170	378	M32×1.5	C
MV5300/0.75	200	320	28	704	385	402	40	203	394	360	170	378	M32×1.5	C
MV6500/0.75	200	320	28	770	385	402	40	203	394	360	205	378	M32×1.5	C
MV10000/0.75	125	380	39	940	452	415	40	205	394	380	280	378	M32×1.5	D

